This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A surgical needle, which comprises:

an elongated needle body defining a longitudinal y axis and x and z axes transverse to the y axis, the elongated needle body including a central shaft and having a first end for attachment to a suture and a second needled end for penetrating tissue, the needled end including lower and upper opposed surfaces and a pair of single side surfaces extending continuously between the lower and upper surfaces and contiguous therewith, the upper surface and side surfaces intersecting to define opposed first and second generally convex side cutting edges extending to a pointed tip, the lower surface extending to a third cutting edge defined at the intersection of the side surfaces and proximal of the pointed tip, the third cutting edge extending in oblique relation relative to the longitudinal axis of the needle body and terminating at the pointed tip.

- 2. (Previously presented) The surgical needle according to claim 1 wherein the upper and lower surfaces are substantially planar.
- 3. (Previously presented) The surgical needle according to claim 2 wherein the needle end defines a first transverse cross-sectional dimension adjacent the central shaft, the first cross-sectional dimension defining a general trapezoidal configuration.
 - 4. (Previously presented) The surgical needle according to claim 3 wherein the

Appl. No. 10/618,994

Amdt. Dated August 17, 2006

Reply to Office Action of May 17, 2006

needle end defines a second transverse cross-sectional dimension adjacent the pointed tip, the second transverse cross-sectional dimension defining a general triangular configuration.

- 5. (Previously presented) The surgical needle according to claim 4 wherein the first cross-sectional dimension defines a dimension along the z-axes corresponding to a first width of the needle end, the first width at least equal to a corresponding shaft width of the central shaft.
- 6. (Previously presented) The surgical needle according to claim 5 wherein the first width is greater than a corresponding shaft width of the central shaft.
- 7. (Previously presented) The surgical needle according to claim 6 wherein the first width is not less than about 1.5 times the shaft width.
- 8. (Previously presented) The surgical needle according to claim 6 wherein the first cross-sectional dimension defines a dimension along the x-axis corresponding to a first height of the needle end, the first height being less than a corresponding shaft height of the central shaft.
- 9. (Previously presented) The surgical needle according to claim 8 wherein the first height is not greater than about 0.5 times the shaft height.

Appl. No. 10/618,994

Amdt. Dated August 17, 2006

Reply to Office Action of May 17, 2006

10. (Previously presented) The surgical needle according to claim 1 wherein the needle body is curved along the longitudinal axis.

- 11. (Previously presented) The surgical needle according to claim 10 wherein the elongated needle shaft defines an angle of curvature ranging from about 80° to about 180°.
- 12. (Previously presented) The surgical needle according to claim 1 wherein the linear cutting edge intersects the upper planar surface at an angle ranging from about 15° to about 30° relative to the longitudinal axis.
- 13. (New) The surgical needle according to claim 1 wherein the single side surfaces are substantially planar.
- 14. (New) The surgical needle according to claim 1 wherein the needled end defines a maximum dimension along the z-axis greater than a corresponding maximum dimension along the z-axis of the central shaft.
 - 15. (New) A surgical needle, which comprises:

an elongated needle body defining a longitudinal y axis, the elongated needle body including a central shaft and having a first end for attachment to a suture and a second needled end for penetrating tissue, the needled end including lower and upper opposed surfaces and single side surfaces extending continuously between the lower and upper surfaces and contiguous

Appl. No. 10/618,994

Amdt. Dated August 17, 2006

Reply to Office Action of May 17, 2006

therewith, the upper surface and side surfaces intersecting to define opposed first and second

generally arcuate side cutting edges extending to a pointed tip, the lower surface extending to a

third cutting edge defined at the intersection of the side surfaces and proximal of the pointed tip,

the third cutting edge extending in oblique relation relative to the longitudinal axis of the needle

body to terminate at the pointed tip, the second needled end defining a maximum dimension

inclusive of the first and second cutting edges greater than a corresponding maximum dimension

of the central shaft.

16. (New) The surgical needle according to claim 15 wherein the side surfaces

are each substantially planar.

17. (New) The surgical needle according to claim 16 wherein the third cutting

edge is substantially linear.

18. (New) The surgical needle according to claim 17 wherein the second needle

end defines a first transverse cross-sectional dimension adjacent the central shaft, the first cross-

sectional dimension defining a general trapezoidal configuration.

19. (New) The surgical needle according to claim 18 wherein the second needle

end defines a second transverse cross-sectional dimension adjacent the pointed tip, the second

transverse cross-sectional dimension defining a general triangular configuration.

Page 8 of 13

Appl. No. 10/618,994 Amdt. Dated August 17, 2006 Reply to Office Action of May 17, 2006

20. (New) The surgical needle according to claim 16 wherein the maximum dimension of the second needled end is at least about 1.5 times the maximum dimension of the central shaft.